

## **VEHICLE CHECK-UP**

## MULTI-POINT INSPECTION

| Date: 06/21/2024 2:00:08 PM R0#: B195726  | LEGEND   May contribute to vehicle efficiency and promote a greener environment  |  |  |  |  |  |  |
|---|--|--|--|--|--|--|--|
| Name: 3j Motors   | Checked and Requires future attention immediate attention  |  |  |  |  |  |  |
| 0dometer: 156785  |  |  |  |  |  |  |  |
| Owner Advantage* #: Owner's Guide checked and update  | ted Checked and completed open field service actions (recalls)   |  |  |  |  |  |  |
| SCHEDULED MAINTENANCE ITEMS DUE*  | EXTERIOR BODY  |  |  |  |  |  |  |
|   | VICED  |  |  |  |  |  |  |
| THE WORKS Engine Air Filter   | Note any   |  |  |  |  |  |  |
| X 0il & Filter Change and Reset  Engine Coolant   | Note any existing exterior   |  |  |  |  |  |  |
| Tire Rotation - n/a in QC <sup>†</sup> Multi-Point Inspection  X  Cabin Air Filter  | body damage or defects on  |  |  |  |  |  |  |
|   | diagram  |  |  |  |  |  |  |
| Fuel Filter Spark Plugs   |  |  |  |  |  |  |  |
| km Scheduled Maintenance  *This is only a partial list of vehicle maintenance items and is NOT all-inclusive,   | SYSTEMS / COMPONENTS   |  |  |  |  |  |  |
| Please consult your Owner's Manual for vehicle-specific maintenance requirements.  FLUID LEVELS SERV  | LIGHTS / WINDSHIELD SERVICED   |  |  |  |  |  |  |
| X Oil and/or fluid leaks  | Operation of horn, interior lights, exterior lamps, turn signals, hazard and brake lamps   |  |  |  |  |  |  |
| OK FILL OK FILL   | Windshield for cracks, chips and pitting   |  |  |  |  |  |  |
| Engine Oil Power Steering Transmission (if equipped with dipstick)  | BELTS / HOSES / MOUNTS SERVICED  |  |  |  |  |  |  |
| X Brake Reservoir X Window Washer X Coolant Recovery Rese   |  |  |  |  |  |  |  |
| WIPER BLADES SERV   | MICED Engine Cooling System, radiator, hoses and clamps  |  |  |  |  |  |  |
| Wiper Test Performed Wiper Blades   | Accessory drive belt(s)  BRAKE SYSTEM SERVICED   |  |  |  |  |  |  |
| BATTERY SERV  | VICED Brake system (including lines, hoses and parking brake)  |  |  |  |  |  |  |
| State of Health Battery Condition   | STEERING / SUSPENSION SERVICED   |  |  |  |  |  |  |
| 100%  | Shocks / struts and other suspension components for leaks and/or damage  |  |  |  |  |  |  |
| Factory spec cold cranking amps Actual cold cranking amps   | X Steering, steering linkages and ball joints (visual)   |  |  |  |  |  |  |
|   | EXHAUST SYSTEM SERVICED  XICED  Exhaust system (leaks, damage, loose parts)  |  |  |  |  |  |  |
| Air filter restriction gauge and housing  | TRANSMISSION / DRIVE AXLE SERVICED   |  |  |  |  |  |  |
| Water in fuel dash light  | Clutch operations (if equipped)  |  |  |  |  |  |  |
| Charge air cooling piping and air intake system   | Constant velocity (CV) drive axle boots (if equipped)  |  |  |  |  |  |  |
| Turbocharger  | Drive shaft, transmission, u-joint and shift linkage (if equipped) and lubricate (as needed)   |  |  |  |  |  |  |
| TIRE / BRAKE WEAR   |  |  |  |  |  |  |  |
| TIRE TREAD 7/32" and greater  | 4/3/2" to 6/3/2" 3/3/2" and less   |  |  |  |  |  |  |
| BRAKE LINING Over 5 mm or 7/82" (Disc) or over 2 mm or 3/32" (Drum) 3   | to 5 mm or 4/82" to 7/82" (Disc) or 1 to 2 mm or 2/32" to 3/82" (Drum)  Less than 3 mm or 4/82" (Disc) or less than 1 mm or 2/32" (Drum) |  |  |  |  |  |  |
| TIRE WEAR INDICATES   | COMMENTS   |  |  |  |  |  |  |
| SERVICED   Wheel balance needed   | SERVICED   |  |  |  |  |  |  |
| LEFT FRONT Ø SERVICED RIGHT FRONT Ø   | SERVICED   |  |  |  |  |  |  |
|   | pth _ 7 _ /32" Tire Age  |  |  |  |  |  |  |
| Tire Wear Pattern / Damage  |  |  |  |  |  |  |  |
| Tire Pressure set to factory-recommended PSI  | set to factory-re commended PSI Service Advisor Alysse Mclean  |  |  |  |  |  |  |
| LEFT REAR Ø SERVICED RIGHT REAR Ø   | SERVICED   |  |  |  |  |  |  |
| X Tire Tread Depth 7 /32" Tire Age X Tire Tread De  | pth 7 /32" Tire Age Customer Signature   |  |  |  |  |  |  |
| Tire Wear Pattern / Damage  Customer Declined   |  |  |  |  |  |  |  |
| Tire Pressure set to factory-recommended PSI Tire Pressure set to factory-recommended PSI Recommended Maintenance  SPARE TIRE   SERVICED Tires should be replaced after six years reparables of treathwear. |  |  |  |  |  |  |  |
| Tire Pressure set to factory-recommended PSI  | after six years regardless of treadwear, if it has not been used.  Your Next Maintenance   |  |  |  |  |  |  |
| BRAKE WEAR INDICATES  |  |  |  |  |  |  |  |
| Brake measurements not taken this service visit   |  |  |  |  |  |  |  |
| · <del></del>   |  |  |  |  |  |  |  |

| DIARC INCOMENIONS WASH THE SERVE FOR |                       |             |
|--------------------------------------|-----------------------|-------------|
| LEFT FRONT                           | SERVICED RIGHT FRONT  | SERVICED    |
|                                      | Brake Lining 8 mm/32" |             |
| LEFT REAR                            | SERVICED RIGHT REAR   | SERVICED +7 |
| Brake Lining 5 mm /32"               |                       |             |

| Mileage | OR | Time |
|---------|----|------|

Tire rotation not included as part of The Works in Quebec.

REV. 03/15 ©2015 Ford Motor Company of Canada, Limited, All Rights Reserved QL-550-E